

# TWISTER



Fixed Output  
or DALI



>50.000 hrs  
at L80B10



L100/CLO  
optional



PowerFactor  
>0.9



Philips  
Fortimo



Philips  
Xitanium



SimpleSet  
Ready

## ABOUT THE TWISTER


The Twister is a robust LED spotlight designed for use on a track rail. Various SLM modules and optics can be applied to create the desired beam width and light output. Choose the RAL color that complements the interior of your company or the daily activities in the workplace. Thanks to effective air circulation and cooling, a lifespan of >50,000 burning hours is guaranteed, even with higher lumen flows.

If you desire a dimmable lighting solution, you can equip the luminaire with a DALI driver. This driver also ensures that any desired light level can be achieved. Alternatively, choose the desired color temperature (Kelvin) with Tunable White.




CE IP20

## FOTOMETRIC DATA




27°



52°

## DIMENSIONS



Bus diameter: 90 mm

Bus length: 135 mm

Driver housing width: 118 mm

## AVAILABLE VERSIONS

CODE	SIZE CM	LUMEN	COLOR	WATT	LM/W	CRI	KELVIN
OC TR TW D090 030 827	13,5 x 9	3.000	827	21.0	143	>80	2700
OC TR TW D090 030 830	13,5 x 9	3.000	830	19.9	151	>80	3000
OC TR TW D090 030 840	13,5 x 9	3.000	840	19.0	158	>80	4000
OC TR TW D090 030 850	13,5 x 9	3.000	850	19.0	158	>80	5000
OC TR TW D090 025 927	13,5 x 9	2.500	927	21.2	118	>90	2700
OC TR TW D090 025 930	13,5 x 9	2.500	930	20.1	124	>90	3000
OC TR TW D090 030 830	13,5 x 9	3.000	830	20.5	146	>90	3000
OC TR TW D090 025 930	13,5 x 9	2.500	930	20.1	125	>90	3000
OC TR TW D090 025 940	13,5 x 9	2.500	940	18.3	137	>90	4000
OC TR TW D090 020 930	13,5 x 9	2.000	930	19.4	103	>90	3000
OC TR TW D090 010 925	13,5 x 9	1.000	925	10.2	98	>90	2500
OC TR TW D090 010 930	13,5 x 9	1.000	930	9.9	101	>90	3000

The table shows the maximum output for each luminaire type. Lower light outputs can always be set according to preference.

### COLORS



### ADDITIONS

